# WAVE OPTICS

Interference of waves of intensity  $I_1$  and  $I_2$ :

resultant intensity, I = I<sub>1</sub> + I<sub>2</sub> +  $2\sqrt{I_1I_2} \cos(\Delta\phi)$  where,  $\Delta\phi$  = phase difference.

 $I_{max} = \left(\sqrt{I_1} + \sqrt{I_2}\right)^2$ For Constructive Interference :  $I_{min} = \left(\sqrt{I_1} - \sqrt{I_2}\right)^2$ For Destructive interference : If sources are incoherent  $I = I_1 + I_2$ , at each point. YDSE: Path difference,  $\Delta p = S_2 P - S_4 P = d \sin \theta$ d < < D =  $\frac{dy}{D}$ if if v << D for maxima,  $\Rightarrow$  y = n $\beta$  n = 0, ±1. ±2 .....  $\Delta p = n\lambda$ for minima  $\Delta p = \Delta p = \begin{cases} (2n-1)\frac{\lambda}{2} & n = 1, 2, 3..., \\ (2n+1)\frac{\lambda}{2} & n = -1, -2, -3..., \\ \end{cases}$  $\Rightarrow \qquad y = \begin{cases} (2n-1)\frac{\beta}{2} & n = 1, 2, 3..., \\ (2n+1)\frac{\beta}{2} & n = -1, -2, -3..., \end{cases}$ where, fringe width  $\beta = \frac{\lambda D}{d}$ Here,  $\lambda$  = wavelength in medium.  $n_{max} = \left| \frac{d}{\lambda} \right|$ Highest order maxima : total number of maxima =  $2n_{max} + 1$  $n_{max} = \left[\frac{d}{\lambda} + \frac{1}{2}\right]$ Highest order minima : total number of minima =  $2n_{max}$ .

Intensity on screen :  $I = I_1 + I_2 + 2\sqrt{I_1I_2} \cos(\Delta \phi)$  where,  $\Delta \phi = \frac{2\pi}{\lambda} \Delta p$ 

If 
$$I_1 = I_2$$
,  $I = 4I_1 \cos^2\left(\frac{\Delta\phi}{2}\right)$ 

YDSE with two wavelengths  $\hat{\lambda}_1 \& \lambda_2$ : The nearest point to central maxima where the bright fringes coincide:  $y = n_1\beta_1 = n_2\beta_2 = Lcm \text{ of } \beta_1 \text{ and } \beta_2$ 

The nearest point to central maxima where the two dark fringes coincide.

y = 
$$(n_1 - \frac{1}{2}) \beta_1 = n_2 - \frac{1}{2} \beta_2$$

#### **Optical path difference**

$$\Delta p_{opt} = \mu \Delta p$$
  

$$\Delta \phi = \frac{2\pi}{\lambda} \Delta p = \frac{2\pi}{\lambda_{vacuum}} \Delta p_{opt.}$$
  

$$\Delta = (\mu - 1) t. \frac{D}{d} = (\mu - 1)t \frac{B}{\lambda}.$$

#### YDSE WITH OBLIQUE INCIDENCE

In YDSE, ray is incident on the slit at an inclination of  $\theta_0$  to the axis of symmetry of the experimental set-up



We obtain central maxima at a point where,  $\Delta p = 0$ .

 $\theta_2 = \theta_0$ . or This corresponds to the point O' in the diagram. Hence we have path difference.

 $d(\sin \theta_0 + \sin \theta) - for points above O$  $\Delta p = \begin{cases} d(\sin \theta_0 - \sin \theta) - \text{for points between O \& O'} \\ d(\sin \theta - \sin \theta_0) - \text{for points below O'} \end{cases}$ ... (8.1)

### THIN-FILM INTERFERENCE

nλ

for interference in reflected light 2µd

for destructive interference

for constructive interference

 $=\begin{cases} 1^{1/\lambda}\\ (n+\frac{1}{2})\lambda \end{cases}$ for interference in transmitted light

for constructive interference

2µd

 $=\begin{cases} n\lambda & \text{for constructive interference} \\ (n + \frac{1}{2})\lambda & \text{for destructive interference} \end{cases}$ 

## Polarisation

• 
$$\mu = \tan$$
 .(brewster's angle)  
 $\theta \rho + \theta_r = 90^{\circ}$ (reflected and refracted rays are mutually perpendicular.)

Law of Malus.

 $I = I_0 \cos^2$ 

 $I = KA^2 \cos^2$ 

**Optical activity** 

$$\left[\alpha\right]_{t^{\circ C}}^{\lambda} = \frac{\theta}{\mathsf{L} \times \mathsf{C}}$$

 $\theta$  = rotation in length L at concentration C.

#### Diffraction

a sin 
$$\theta$$
 = (2m + 1)/2 for maxima. where m = 1, 2, 3...

 $\sin \theta = \frac{m\lambda}{a}$ , m = ± 1, ± 2, ± 3..... for minima.

Linear width of central maxima =  $\frac{2d\lambda}{a}$ 

Angular width of central maxima =  $\frac{2\lambda}{a}$ 

• 
$$I = I_0 \left[ \frac{\sin \beta / 2}{\beta / 2} \right]^2$$
 where  $\beta = \frac{\pi a \sin \theta}{\lambda}$ 

• Resolving power.

$$\mathsf{R} = \frac{\lambda}{\lambda_2 - \lambda_1} = \frac{\lambda}{\Delta \lambda}$$

where , 
$$\lambda = \frac{\lambda_1 + \lambda_2}{2}$$
 ,  $\Delta \lambda = \lambda_2 - \lambda_1$