SET-

Series EHEFG

प्रश्न-पत्र कोड Q.P. Code

रोल न					
Roll	No				
		-			
			7: 3:		(0)

Candidates must write the Q.P. Code on the title page of the answer-book.

COMPUTER SCIENCE

Time allowed: 3 hours Maximum Marks: 70

- Please check that this question paper contains 15 printed pages.
- Q.P. Code given on the right hand side of the question paper should be written on the title page of the answer-book by the candidate.
- Please check that this question paper contains **35** questions.
- Please write down the serial number of the question in the answer book before attempting it.
- 15 minute time has been allotted to read this question paper. The question paper will be distributed at 10.15 a.m. From 10.15 a.m. to 10.30 a.m., the candidates will read the question paper only and will not write any answer on the answer-book during this period.





α 1	(T) . •	
General	Instructions	:

- (i) This question paper contains five sections, **Section** A to E.
- (ii) All questions are compulsory.
- (iii) Section A have 18 questions carrying 1 mark each.
- (iv) Section B has 7 Very Short Answer type questions carrying 2 marks each.
- (v) Section C has 5 Short Answer type questions carrying 3 marks each.
- (vi) Section D has 3 Long Answer type questions carrying 5 marks each.
- (vii) Section E has 2 questions carrying 4 marks each. One internal choice is given in Q. 34 and 35, against Part (iii) only.
- (viii) All programming questions are to be answered using Python Language only.

SECTION - A

1. State True or False.

"Identifiers are names used to identify a variable, function in a program".

- 2. Which of the following is a valid keyword in Python?
 - (a) false

(b) return

(c) non_local

- (d) none
- 3. Given the following Tuple

Tup=(10, 20, 30, 50)

Which of the following statements will result in an error?

(a) print(Tup[0])

(b) Tup.insert (2,3)

1

1

1

1

1

- (c) print(Tup[1:2])
- (d) print(len(Tup))
- 4. Consider the given expression :

5<10 and 12>7 or not 7>4

Which of the following will be the correct output, if the given expression is evaluated?

(a) True

(b) False

(c) NONE

- (d) NULL
- 5. Select the correct output of the code:

S= "Amrit Mahotsav @ 75"

A=S.partition (" ")

print (a)

- (a) ('Amrit Mahotsav','@','75')
- (b) ['Amrit', 'Mahotsav', '@', '75']
- (c) ('Amrit', 'Mahotsav @ 75')
- (d) ('Amrit', '', 'Mahotsav @ 75')



6.	Whi file	ch of the following mode keeps th	ne file	offset position at the end of the	1
	(a)	· r+	(b)	r	
	(c)	W	(d)	a	
	(0)	v	(u)	u .	
7.	Fill	in the blank.			1
			eleme	ents of a list in ascending order.	
	(a)	sort()	(b)	arrange()	
	(c)	ascending()	(d)	asort()	
	` /	3 . ,	` /	, ,	
8.	Whi	ch of the following operators will	retur	n either True or False ?	1
	(a)	+=	(b)	! =	
	(c)	=	(d)	*=	
9.	Whi	ch of the following statement(s)	woul	d give an error after executing	
		following code?		8	1
		Stud={"Murugan":100, "Mit	chu":	95} # Statement 1	
		<pre>print (Stud[95])</pre>		# Statement 2	
		Stud ["Murugan"]=99		# Statement 3	
		<pre>print(Stud.pop())</pre>		# Statement 4	
		print(Stud)		# Statement 5	
	(a)	Statement 2	(b)	Statement 3	
	(c)	Statement 4	(d)	Statements 2 and 4	
	` /		` /		
10.	Fill	in the blank.			1
		_ is a number of tuples in a relat	ion.		
	(a)	Attribute	(b)	Degree	
	(c)	Domain	(d)	Cardinality	
	` ,		` ′	-	
11.	The	syntax of seek() is :			1
		e object.seek(offset[,refe	erenc	ce point])	
	Wha	at is the default value of referer	nce p	ooint?	
	(a)	0	(b)	1	
	(c)	2	(d)	3	
	(-)		()		
12.	Fill	in the blank:			1
		clause is used with SELECT	state	ment to display data in a sorted	
	form	n with respect to a specified colum		1 0	
	(a)	WHERE	(b)	ORDER BY	
	(c)	HAVING	(d)	DISTINCT	
	` /			ra ser	
91		< :	3	P.T.	0.

13.	Fill	in the blank:			1
			nmuni	cation or unicast communication	
	suci (a)	n as radar and satellite. INFRARED WAVES	(b)	BLUETOOTH	
	(c)	MICROWAVES	(d)	RADIOWAVES	
	(0)	HICKOMAVED	(u)	NADIOWAVES	
14.	Wha	at will the following expression print (4+3*5/3-5%2)	be eval	uated to in Python?	1
	(a)	8.5	(b)	8.0	
	(c)	10.2	(d)	10.0	
15.	Whi	ich function returns the sum of a	all elen	nents of a list?	1
	(a)	count()	(b)	sum()	
	(c)	total()	(d)	add()	
16.	fetc	hall() method fetches all rows in	ı a resu	ılt set and returns a :	1
	(a)	Tuple of lists	(b)	List of tuples	
	(c)	List of strings	(d)	Tuple of strings	
	-	17 and 18 are ASSERTION (A)	and RI	EASONING (R) based questions.	
	(a) (b)	Both (A) and (R) are true and (Both (A) and (R) are true and (A).		he correct explanation for (A). s not the correct explanation for	
	(c)	(A) is true but (R) is false.			
	(d)	(A) is false but (R) is true.			
17.	Ass	ertion (A): To use a function import the module.	from a	a particular module, we need to	1
	Rea	ason (R) : import statement can before using a function from th		ritten anywhere in the program, dule.	
18.		ertion (A): A stack is a LIFO s ason (R): Any new element positioned at the index after the	push	ed into the stack always gets	1

SECTION - B

19. Atharva is a Python programmer working on a program to find and return the maximum value from the list. The code written below has syntactical errors. Rewrite the correct code and underline the corrections made.

2

```
def max_num (L) :
    max=L(0)
    for a in L :
        if a > max
        max=a
    return max
```

20. (a) Differentiate between wired and wireless transmission.

2

${ m OR}$

(b) Differentiate between URL and domain name with the help of an appropriate example.

2

1

1

21. (a) Given is a Python list declaration:

Listofnames=["Aman", "Ankit", "Ashish", "Rajan", "Rajat"]

```
Write the output of:
```

print (Listofnames [-1:-4:-1])

(b) Consider the following tuple declaration:
tup1=(10,20,30,(10,20,30),40)

tupi-(10,20,30,(10,20,30)

```
Write the output of :
print(tupl.index(20))
```

- 22. Explain the concept of "Alternate Key" in a Relational Database Management System with an appropriate example.
 - 2

23. (a) Write the full forms of the following:

2

- (i) HTML
- (ii) TCP
- (b) What is the need of Protocols?
- 24. (a) Write the output of the code given below:

2

```
def short_sub (lst,n) :
    for i in range (0,n) :
        if len (lst)>4:
            lst [i]=lst [i]+lst[i]
        else:
            lst[i]=lst[i]
subject=['CS','HINDI','PHYSICS','CHEMISTRY','MATHS']
short_sub(subject,5)
print(subject)
```

OR

(b) Write the output of the code given below:

```
a =30
def call (x):
    global a
    if a%2==0:
        x+=a
    else:
        x-=a
    return x
x=20
print(call(35),end="#")
```

print(call(40), end= "@")

25. (a) Differentiate between CHAR and VARCHAR data types in SQL with appropriate example.

OR

(b) Name any two DDL and any two DML commands.

 $\mathbf{2}$

2

2

SECTION - C

26. (a) Consider the following tables – LOAN and BORROWER:

1 + 2

Table: LOAN

LOAN_NO	B_NAME	AMOUNT
L-170	DELHI	3000
L-230	KANPUR	4000

Table: BORROWER

CUST_NAME	LOAN_NO
JOHN	L-171
KRISH	L-230
RAVYA	L-170

How many rows and columns will be there in the natural join of these two tables?



(b) Write the output of the queries (i) to (iv) based on the table, WORKER given below:

TABLE: WORKER

W_ID	F_NAME	L_NAME	CITY	STATE
102	SAHIL	KHAN	KANPUR	UTTAR PRADESH
104	SAMEER	PARIKH	ROOP NAGAR	PUNJAB
105	MARY	JONES	DELHI	DELHI
106	MAHIR	SHARMA	SONIPAT	HARYANA
107	ATHARVA	BHARDWAJ	DELHI	DELHI
108	VEDA	SHARMA	KANPUR	UTTAR PRADESH

- (i) SELECT F_NAME, CITY FROM WORKER ORDER BY STATE DESC;
- (ii) SELECT DISTINCT (CITY) FROM WORKER;
- (iii) SELECT F_NAME, STATE FROM WORKER WHERE L_NAME LIKE '_HA%';
- (iv) SELECT CITY, COUNT (*) FROM WORKER GROUP BY CITY;
- 27. (a) Write the definition of a Python function named LongLines() which reads the contents of a text file named 'LINES.TXT' and displays those lines from the file which have at least 10 words in it. For example, if the content of 'LINES.TXT' is as follows:

Once upon a time, there was a woodcutter

He lived in a little house in a beautiful, green wood.

One day, he was merrily chopping some wood.

He saw a little girl skipping through the woods, whistling happily.

The girl was followed by a big gray wolf.

Then the function should display output as:

He lived in a little house in a beautiful, green wood.

He saw a little girl skipping through the woods, whistling happily.

OR



(b) Write a function count_Dwords() in Python to count the words ending with a digit in a text file "Details.txt".

3

2

1

Example:

If the file content is as follows:

On seat2 VIP1 will sit and

On seat1 VVIP2 will be sitting

Output will be:

Number of words ending with a digit are 4

28. (a) Write the outputs of the SQL queries (i) to (iv) based on the relations COMPUTER and SALES given below:

Table: COMPUTER

COMPANY PROD ID PROD_NAME **PRICE** TYPE P001 **MOUSE** 200 LOGITECH **INPUT** P002 LASER PRINTER 4000 **CANON** OUTPUT P003 KEYBOARD 500 LOGITECH INPUT **JOYSTICK** P004 1000 IBALL **INPUT** P005 **SPEAKER** 1200 **CREATIVE OUTPUT** DESKJET PRINTER P006 4300 **CANON** OUTPUT

Table: SALES

PROD_ID	QTY_SOLD	QUARTER
P002	4	1
P003	2	2
P001	3	2
P004	2	1

- (i) SELECT MIN(PRICE), MAX(PRICE) FROM COMPUTER;
- (ii) SELECT COMPANY, COUNT(*) FROM COMPUTER GROUP BY COMPANY HAVING COUNT(COMPANY) > 1;
- (iii) SELECT PROD_NAME, QTY_SOLD FROM COMPUTER C, SALES S WHERE C.PROD_ID=S.PROD_ID AND TYPE = 'INPUT';
- (iv) SELECT PROD_NAME, COMPANY, QUARTER FROM COMPUTER
 C, SALES S WHERE C.PROD_ID=S. PROD_ID;
- (b) Write the command to view all databases.

29. Write a function EOReplace() in Python, which accepts a list L of numbers. Thereafter, it increments all even numbers by 1 and decrements all odd numbers by 1.

3

Example:

If Sample Input data of the list is:

L=[10,20,30,40,35,55]

Output will be:

L=[11,21,31,41,34,54]

30. (a) A list contains following record of customer:

[Customer name, Room Type]

Write the following user defined functions to perform given operations on the stack named 'Hotel':

- (i) Push_Cust() To Push customers' names of those customers who are staying in 'Delux' Room Type.
- (ii) Pop_Cust() To Pop the names of customers from the stack and display them. Also, display "Underflow" when there are no customers in the stack.

For example:

If the lists with customer details are as follows:

["Siddarth", "Delux"]
["Rahul", "Standard"]

["Jerry", "Delux"]

The stack should contain

Jerry

Siddharth

The output should be:

Jerry

Siddharth

Underflow

OR.

(b) Write a function in Python, Push (Vehicle) where, Vehicle is a dictionary containing details of vehicles — {Car_Name: Maker}.

The function should push the name of car manufactured by 'TATA' (including all the possible cases like Tata, TaTa, etc.) to the stack.

For example:

If the dictionary contains the following data:

Vehicle={"Santro":"Hyundai", "Nexon":"TATA", "Safari":"Tata"}

The stack should contain

Safari

Nexon



SECTION - D

31. Quickdev, an IT based firm, located in Delhi is planning to set up a network for its four branches within a city with its Marketing department in Kanpur. As a network professional, give solutions to the questions (i) to (v), after going through the branches locations and other details which are given below:

DELHI BRANCH

BRANCH A

BRANCH B

BRANCH D

KANPUR BRANCH

MARKETING DEPT.

Distance between various branches is as follows:

Branch	Distance
Branch A to Branch B	40 m
Branch A to Branch C	80 m
Branch A to Branch D	65 m
Branch B to Branch C	30 m
Branch B to Branch D	35 m
Branch C to Branch D	15 m
Delhi Branch to Kanpur	300 km

Number of computers in each of the branches :

Branch	Number of Computers
Branch A	15
Branch B	25
Branch C	40
Branch D	115

(i) Suggest the most suitable place to install the server for the Delhi branch with a suitable reason.



- (ii) Suggest an ideal layout for connecting all these branches within Delhi.
- 1
- (iii) Which device will you suggest, that should be placed in each of these branches to efficiently connect all the computers within these branches?

1

(iv) Delhi firm is planning to connect to its Marketing department in Kanpur which is approximately 300 km away. Which type of network out of LAN, WAN or MAN will be formed? Justify your answer.

1

(v) Suggest a protocol that shall be needed to provide help for transferring of files between Delhi and Kanpur branch.

1

32. (a) What possible output(s) are expected to be displayed on screen at the time of execution of the following program:

```
import random
M=[5,10,15,20,25,30]
for i in range(1,3):
    first=random.randint(2,5)- 1
    sec=random.randint(3,6)- 2
    third=random.randint(1,4)
    print(M[first],M[sec],M[third],sep="#")
```

10#25#15 20#25#25 (ii) 5#25#20 25#20#15

(iii) 30#20#20 20#25#25

(i)

(iv) 10#15#25# 15#20#10#

2

(b) The code given below deletes the record from the table employee which contains the following record structure:

E_code - String
E_name - String
Sal - Integer
City - String

Note the following to establish connectivity between Python and MySQL:

- Username is root
- Password is root
- The table exists in a MySQL database named emp.
- The details (E_code, E_name, Sal, City) are the attributes of the table.

Write the following statements to complete the code:

Statement 1 – to import the desired library.

Statement 2 – to execute the command that deletes the record with E code as 'E101'.

Statement 3- to delete the record permanently from the database.

```
import _____ as mysql  # Statement 1

def delete():
    mydb=mysql.connect(host="localhost",user="root",
    passwd="root",database="emp")

mycursor=mydb.cursor()
    ____ # Statement 2
    ____ # Statement 3

print ("Record deleted")
```

 \mathbf{OR}

(a) Predict the output of the code given below:

```
def makenew(mystr):
    newstr=""
    count=0
    for i in mystr:
        if count%2!=0:
            newstr=newstr+str(count)
    else :
        if i.lower():
            newstr=newstr+i.upper()
        else:
            newstr=newstr+i
        count+=1
    print(newstr)
makenew("No@1")
```

2

(b) The code given below reads the following records from the table employee and displays only those records who have employees coming from city 'Delhi':

```
E_code - String
E_name - String
Sal - Integer
City - String
```

Note the following to establish connectivity between Python and MySQL:

- Username is root.
- Password is root
- The table exists in a MySQL database named emp.
- The details (E_code, E_name, Sal, City) are the attributes of the table.

Write the following statements to complete the code:

Statement 1 -to import the desired library.

Statement 2 – to execute the query that fetches records of the employees coming from city 'Delhi'.

Statement 3 – to read the complete data of the query (rows whose city is Delhi) into the object named details, from the table employee in the database.

33. (a) Write one difference between CSV and text files.

Write a program in Python that defines and calls the following user defined functions:

- (i) COURIER_ADD(): It takes the values from the user and adds the details to a csv file 'courier.csv'. Each record consists of a list with field elements as cid, s_name, Source, destination to store Courier ID, Sender name, Source and destination address respectively.
- (ii) COURIER_SEARCH(): Takes the destination as the input and displays all the courier records going to that destination.

OR

(b) Why it is important to close a file before exiting?

Write a program in Python that defines and calls the following user defined functions:

- (i) Add_Book(): Takes the details of the books and adds them to a csv file 'Book.csv'. Each record consists of a list with field elements as book_ID, B_name and pub to store book ID, book name and publisher respectively.
- (ii) Search_Book(): Takes publisher name as input and counts and displays number of books published by them.

SECTION - E

34. The school has asked their estate manager Mr. Rahul to maintain the data of all the labs in a table LAB. Rahul has created a table and entered data of 5 labs.

LABNO	LAB_NAME	INCHARGE	CAPACITY	FLOOR
L001	CHEMISTRY	Daisy	20	I
L002	BIOLOGY	Venky	20	II
L003	MATH	Preeti	15	Ι
L004	LANGUAGE	Daisy	36	III
L005	COMPUTER	Mary Kom	37	II

Based on the data given above answer the following questions:

- (i) Identify the columns which can be considered as Candidate keys.
- (ii) Write the degree and cardinality of the table.
- (iii) Write the statements to:
 - (a) Insert a new row with appropriate data.
 - (b) Increase the capacity of all the labs by 10 students which are on 'I' Floor.

OR

(Option for part (iii) only)

- (iii) Write the statements to:
 - (a) Add a constraint PRIMARY KEY to the column LABNO in the table.
 - (b) Delete the table LAB.

2

1

1

2

5

35. Shreyas is a programmer, who has recently been given a task to write a user defined function named write_bin() to create a binary file called Cust_file.dat containing customer information — customer number (c_no), name (c_name), quantity (qty), price (price) and amount (amt) of each customer.

The function accepts customer number, name, quantity and price. Thereafter, it displays the message 'Quantity less than 10..... Cannot SAVE', if quantity entered is less than 10. Otherwise the function calculates amount as price * quantity and then writes the record in the form of a list into the binary file.

```
import pickle
def write bin():
            #Statement 1
  bin file=
  while True:
    c no=int(input("enter customer number"))
    c name=input("enter customer name")
    qty=int(input("enter qty"))
    price=int(input("enter price"))
               #Statement 2
      print("Quantity less than 10..Cannot SAVE")
    else:
      amt=price * qty
      c detail=[c no, c name, qty, price, amt]
             #Statement 3
      ans=input("Do you wish to enter more records y/n")
      if ans.lower() == 'n':
                 #Statement 4
                 #Statement 5
                 #Statement 6
```

- (i) Write the correct statement to open a file 'Cust_file.dat' for writing the data of the customer.
- (ii) Which statement should Shreyas fill in Statement 2 to check whether quantity is less than 10.
- (iii) Which statement should Shreyas fill in Statement 3 to write data to the binary file and in Statement 4 to stop further processing if the user does not wish to enter more records.

OR

(Option for part (iii) only)

(iii) What should Shreyas fill in Statement 5 to close the binary file named Cust_file.dat and in Statement 6 to call a function to write data in binary file?



1

1

2

Marking Scheme Strictly Confidential (For Internal and Restricted use only) Senior School Certificate Examination, 2023

SUBJECT NAME: COMPUTER SCIENCE (SUBJECT CODE: 083) (PAPER CODE: 91)

General Instructions:

- You are aware that evaluation is the most important process in the actual and correct assessment of the candidates. A small mistake in evaluation may lead to serious problems which may affect the future of the candidates, education system and teaching profession. To avoid mistakes, it is requested that before starting evaluation, you must read and understand the spot evaluation guidelines carefully.
- "Evaluation policy is a confidential policy as it is related to the confidentiality of the examinations conducted, Evaluation done and several other aspects. Its' leakage to public in any manner could lead to derailment of the examination system and affect the life and future of millions of candidates. Sharing this policy/document to anyone, publishing in any magazine and printing in News Paper/Website etc may invite action under various rules of the Board and IPC."
- Evaluation is to be done as per instructions provided in the Marking Scheme. It should not be done according to one's own interpretation or any other consideration. Marking Scheme should be strictly adhered to and religiously followed. However, while evaluating, answers which are based on latest information or knowledge and/or are innovative, they may be assessed for their correctness otherwise and due marks be awarded to them. In class-X, while evaluating two competency-based questions, please try to understand given answer and even if reply is not from marking scheme but correct competency is enumerated by the candidate, due marks should be awarded.
- The Marking scheme carries only suggested value points for the answers. These are in the nature of Guidelines only and do not constitute the complete answer. The students can have their own expression and if the expression is correct, the due marks should be awarded accordingly.
- The Head-Examiner must go through the first five answer books evaluated by each evaluator on the first day, to ensure that evaluation has been carried out as per the instructions given in the Marking Scheme. If there is any variation, the same should be zero after delibration and discussion. The remaining answer books meant for evaluation shall be given only after ensuring that there is no significant variation in the marking of individual evaluators.
- **6** Evaluators will mark($\sqrt{}$) wherever answer is correct. For wrong answer CROSS 'X" be marked. Evaluators will not put right ($\sqrt{}$)while evaluating which gives an impression that answer is correct and no marks are awarded. **This is most common mistake which evaluators are committing.**

[Sub Code: 083 Series: HFG1E Paper Code: 91 SET-4] [Page #1/37]

7	If a question has parts, please award marks on the right-hand side for each part. Marks awarded for different parts of the question should then be totaled up and written in the left-hand margin and encircled. This may be followed strictly.
8	If a question does not have any parts, marks must be awarded in the left-hand margin and encircled. This may also be followed strictly.
9	If a student has attempted an extra question, answer of the question deserving more marks should be retained and the other answer scored out with a note "Extra Question".
10	No marks to be deducted for the cumulative effect of an error. It should be penalized only once.
11	A full scale of marks(example 0 to 80/70/60/50/40/30 marks as given in Question Paper) has to be used. Please do not hesitate to award full marks if the answer deserves it.
12	Every examiner has to necessarily do evaluation work for full working hours i.e., 8 hours every day and evaluate 20 answer books per day in main subjects and 25 answer books per day in other subjects (Details are given in Spot Guidelines). This is in view of the reduced syllabus and number of questions in question paper.
13	 Ensure that you do not make the following common types of errors committed by the Examiner in the past:- Leaving answer or part thereof unassessed in an answer book. Giving more marks for an answer than assigned to it. Wrong totaling of marks awarded on an answer. Wrong transfer of marks from the inside pages of the answer book to the title page. Wrong question wise totaling on the title page. Wrong totaling of marks of the two columns on the title page. Wrong grand total. Marks in words and figures not tallying/not same. Wrong transfer of marks from the answer book to online award list. Answers marked as correct, but marks not awarded. (Ensure that the right tick mark is correctly and clearly indicated. It should merely be a line. Same is with the X for incorrect answer.) Half or a part of answer marked correct and the rest as wrong, but no marks awarded.
14	While evaluating the answer books if the answer is found to be totally incorrect, it should be marked as cross (X) and awarded zero (0)Marks.
15	Any un assessed portion, non-carrying over of marks to the title page, or totaling error detected by the candidate shall damage the prestige of all the personnel engaged in the evaluation work as also of the Board. Hence, in order to uphold the prestige of all concerned, it is again reiterated that the instructions be followed meticulously and judiciously.

[Sub Code: 083 Series: HFG1E Paper Code: 91 SET-4] [Page #2/37]

16	The Examiners should acquaint themselves with the guidelines given in the "Guidelines for spot Evaluation" before starting the actual evaluation.
17	Every Examiner shall also ensure that all the answers are evaluated, marks carried over to the title page, correctly totaled and written in figures and words.
18	The candidates are entitled to obtain a photocopy of the Answer Book on request on payment of the prescribed processing fee. All Examiners/Additional Head Examiners/Head Examiners are once again reminded that they must ensure that evaluation is carried out strictly as per value points for each answer as given in the Marking Scheme.

General Instructions:

- (i) This question paper contains five sections, **Section A to E**.
- (ii) All questions are compulsory.
- (iii) **Section A** have **18** questions carrying 1 mark each.
- (iv) **Section B** has **7** Very Short Answer type questions carrying **2** marks each.
- (v) **Section C** has **5** Short Answer type questions carrying **3** marks each.
- (vi) **Section D** has **3** Long Answer type questions carrying **5** marks each.
- (vii) **Section E** has **2** questions carrying **4** marks each. **One** internal choice is given in **Q.34 and 35**, against Part (iii) only.
- (viii) All programming questions are to be answered using Python Language only.

[Sub Code: 083 Series: HFG1E Paper Code: 91 SET-4] [Page #3/37]

		SECTION - A						
	_							
1.		State True or False.	1					
	Ans	"Identifiers are names used to identify a variable, function in a program". True						
	Alla	(1 mark for writing correct answer)						
		(Timark for writing correct unswer)						
2.		Which of the following is a valid keyword in Python ?	1					
		(a) false (b) return						
		c) non_local (d) none						
	Ans	(b) return						
		(1 mark for writing correct answer)						
3.		Given the following Tuple	1					
		Tup= (10, 20, 30, 50)	-					
		Which of the following statements will result in an error?						
		(a) print (Tup[0]) (b) Tup.insert (2, 3)						
		(C) print (Tup [1:2]) (d) print (len (Tup))						
	Ans	(b) Tup.insert (2, 3)						
		(1 mark for writing correct answer)						
4.		Consider the given expression :						
		5<10 and 12>7 or not 7>4						
		Which of the following will be the correct output, if the given expression is						
		evaluated?						
		(a) True (b) False						
	A	(c) NONE (d) NULL						
	Ans	(a) True						
		(1 mark for writing correct answer)						
5.		Select the correct output of the code:	1					
		S= "Amrit Mahotsav @ 75"						
		A=S.partition (" ")						
		print (a)						
		(a) ('Amrit Mahotsav','@','75')						
		(b) ['Amrit','Mahotsav','@','75']						
		(C) ('Amrit', 'Mahotsav @ 75')						
		(d) ('Amrit','' , 'Mahotsav @ 75')						
	Ans	(d) ('Amrit', '', 'Mahotsav @ 75')						
L		I						

[Sub Code: 083 Series: HFG1E Paper Code: 91 SET-4] [Page #4/37]

		(1 mark for writing correct answer)	
		OR (1 mark for mentioning Error in code OR no correct option)	
		Note:	
		print(A) is wrongly typed as print(a)	
6.		Which of the following mode keeps the file offset position at the end of the	1
		file ?	
		(a) r+ (b) r	
		(c) w (d) a	
	Ans	(d) a	
		(1 mark for writing correct answer)	
7.		Fill in the blank.	1
		function is used to arrange the elements of a list in ascending order.	
		(a) sort() (b) arrange()	
		(c) ascending() (d) asort()	
	Ans	(a) sort()	
		(1 mark for writing correct answer)	
8.		Which of the following operators will return either True or False?	1
		(a) += (b) !=	
		(c) = (d) *=	
	Ans	(b) !=	
		(1 mark for writing correct answer) OR	
		(1 mark for mentioning No option OR Error in question)	
		Note:	
		an operator does not return any values until it is part of an expression	

[Sub Code: 083 Series: HFG1E Paper Code: 91 SET-4] [Page #5/37]

9.		Which of the following statement(s) would give an error after executing the following code? Stud={"Murugan" : 100, "Mithu" : 95} # Statement 1 print (Stud[95]) # Statement 2 Stud ["Murugan"]=99 # Statement 3 print(Stud.pop()) # Statement 4	1
		print(Stud) # Statement 5	
		(a) Statement 2 (b) Statement 3	
		(c) Statement 4 (d) Statements 2 and 4	
	Ans	(a) Statement 2	
		OR	
		(d) Statements 2 and 4	
		(1 mark for writing correct answer as (a))	
		OR (1 mark for writing correct answer as (d))	
		OR	
		(1 mark for writing (a) and (c) as the correct answers)	
		OR	
		(Only ½ mark for writing (c) as the correct answer)	
10.		Fill in the blank.	1
		is a number of tuples in a relation.	
		(a) Attribute (b) Degree	
		(c) Domain (d) Cardinality	
	Ans	(d) Cardinality	
		(1 mark for writing correct answer)	
11.		The syntax of seek () is:	1
		<pre>file_object.seek (offset[, reference_point])</pre>	
		What is the default value of reference_point?	
		(a) 0 (b) 1	
		(c) 2 (d) 3	
	Ans	(a) 0	
		(1 mark for writing correct answer)	

[Sub Code: 083 Series: HFG1E Paper Code: 91 SET-4] [Page #6/37]

12.		Fill in the blank :	1			
		clause is used with SELECT statement to display data in a sorted				
		form with respect to a specified column.				
		(a) WHERE (b) ORDER BY				
		(c) HAVING (d) DISTINCT				
	Ans	(b) ORDER BY				
		(1 mark for writing correct answer)				
13.		Fill in the blank :	1			
		is used for point-to-point communication or unicast communication				
		such as radar and satellite.				
		(a) INFRARED WAVES (b) BLUETOOTH				
		(c) MICROWAVES (d) RADIOWAVES				
	Ans	(c) MICROWAVES				
		OR				
		(d) RADIOWAVES				
	(1 mark for writing correct answer as (c) MICROWAVES)					
		OR (1 mark for writing correct answer as (d) PADIOWAVES)				
		(1 mark for writing correct answer as (d) RADIOWAVES)				
14.		What will the following expression be evaluated to in Python?				
		print(4+3*5/3-5%2)				
		(a) 8.5 (b) 8.0				
		(c) 10.2 (d) 10.0				
	Ans	(b) 8.0				
		(1 mark for writing correct answer)				
15.		Which function returns the sum of all elements of a list?	1			
		(a) count() (b) sum()				
		(C) total() (d) add()				
	Ans	(b) sum()				
		(1 mark for writing correct answer)				
16.		fetchall() method fetches all rows in a result set and returns a :	1			
		(a) Tuple of lists (b) List of tuples				
		(c) List of strings (d) Tuple of strings				
	Ans.	(b) List of tuples				
		(1 mark for writing correct answer)				

[Sub Code: 083 Series: HFG1E Paper Code: 91 SET-4] [Page #7/37]

Q. 17	' and 1	8 are ASSERTION (A) and REASONING (R) based questions.				
Mark	the co	rrect choice as				
(a) Bo	(a) Both (A) and (R) are true and (R) is the correct explanation for (A).					
(b) Bo	oth (A)	and (R) are true and (R) is not the correct explanation for (A).				
(c) (A) is tru	e but (R) is false.				
(d) (A	ı) is fal	se but (R) is true.				
17.	17. Assertion (A): To use a function from a particular module, we need to					
		import the module.				
	Reason (R): import statement can be written anywhere in the program,					
	before using a function from that module.					
	Ans.	(b) Both (A) and (R) are true and (R) is not the correct explanation for (A)				
		(1 mark for writing correct answer)				
		OR				
		($\frac{1}{2}$ mark for writing (a) as the correct option)				
18.		Assertion (A): A stack is a LIFO structure.	1			
		Reason (R): Any new element pushed into the stack always gets positioned				
		at the index after the last existing element in the stack				
	Ans	(c) (A) is true but (R) is false.				
		(1 mark for writing (c) as the correct option)				
		OR				
		(1 mark for writing (b) as the correct option) OR				
		(1 mark for writing (a) as the correct option)				
		(1 mark yer writing (a) as the correct operally				
		SECTION B				
19.		Atharva is a Python programmer working on a program to find and return the	2			
		maximum value from the list. The code written below has syntactical errors.				
		Rewrite the correct code and underline the corrections made.				
		def max_num (L) :				
		max=L(0)				
		for a in L :				
		if a > max				
		max=a				
		return max				

[Sub Code: 083 Series: HFG1E Paper Code: 91 SET-4] [Page #8/37]

		<pre>def max_num (L) : max=L[0] for a in L: if a > max:</pre>	
		for a in L: if a > max: max=a return max (1½ marks for correcting all 3 mistakes) (½ mark for underlining the corrections)	
		max=a return max (1½ marks for correcting all 3 mistakes) (½ mark for underlining the corrections)	
		return max (1½ marks for correcting all 3 mistakes) (½ mark for underlining the corrections)	
		(1½ marks for correcting all 3 mistakes) (½ mark for underlining the corrections)	
		(½ mark for underlining the corrections)	
		,	
		OR	
		(1 mark for correcting only 2 mistakes)	
		(½ mark for underlining the corrections)	
		OR	
		(½ mark for correcting only 1 mistake)	
		(½ mark for underlining the correction)	
20.	(a)	Differentiate between wired and wireless transmission.	2
	Ans	In case of wired or guided transmission, there is a physical link made of	
		wire/cable through which data in terms of signals are propagated between	
		the nodes. These are usually metallic cable, fiber-optic cable, etc.	
		In case of wireless or unguided transmission, data travels in air in terms of	
		electromagnetic waves using an antenna. These are usually bluetooth, microwaves, infrared, radio waves, etc.	
		OR	
		In case of wired transmission, the devices in the network are connected using cables.	
		Wireless transmission uses waves/rays to connect devices.	
		OR	
		Any other valid difference (any one)	
		(2 marks for differentiating with or without examples) OR	
		(1 mark each for defining each type with or without examples)	
		OR	
		(½ mark each for mentioning example of each type)	

[Sub Code: 083 Series: HFG1E Paper Code: 91 SET-4] [Page #9/37]

		OR	
	(b)	Differentiate between URL and domain name with the help of an	
	Ans	appropriate example. URL is the complete internet address of a webpage while Domain name is	2
	AIIS	just the name of the organisation/individual entity along with top-level	Z
		internet domains such as com, edu, gov, etc.	
		Example:	
		URL: https://www.ncert.nic.in/textbook/textbook.htm	
		Domain Name: ncert.nic.in OR www.ncert.nic.in	
		OR	
		any valid definition along with examples	
		(2 marks for writing any one difference with the help of examples) OR	
		(2 marks for writing examples to differentiate correctly)	
		OR	
		(1 mark only for writing any one difference without examples)	
21.	(a)	Given is a Python list declaration :	1
		Listofnames=["Aman", "Ankit", "Ashish", "Rajan", "Rajat"]	
		Write the output of:	
		print (Listofnames [-1:-4:-1])	
	Ans	['Rajat', 'Rajan', 'Ashish']	
		(1 mark for writing the correct output with/without formatting)	
		OR	
		(½ mark for mentioning the correct names - 'Ashish', 'Rajan', 'Rajat'	
		but not in correct order)	
	(b)	Consider the following tuple declaration :	1
		tup1=(10,20,30,(10,20,30),40)	
		Write the output of:	
	_	<pre>print(tupl.index(20))</pre>	
	Ans		
		(1 mark for writing the correct output)	

[Sub Code: 083 Series: HFG1E Paper Code: 91 SET-4] [Page #10/37]

22.			of ''Alternate Key'' in a F with an appropriate exar		2
	Ans	Alternate Keys are a been used as a Prima Example:	•	RDBMS table, which have not	
		RegNo	AadhaarNo	Name	
		123456	123456789012	Abraham Sen	
		123458	123456789123	Umeed Singh	
				dhaarNo can be used as a Key then AadhaarNo is the	
		OR (1 mark for writing OR	ing Alternate Keys with example of Alternate K iting the definition of A	eys without any explanation)	
23.	(a)	Write the full forms (i) HTML (ii) TCP	of the following:		2
	Ans	(i) HTML: Hyper To	ext Markup Language on Control Protocol		
		(½ mark for writing	g each of the two full for	rms)	
	(b)	What is the need of	Protocols ?		
	Ans	OR	d for communication betw nition/explanation of prot	·	
			any one need OR definit		

[Sub Code: 083 Series: HFG1E Paper Code: 91 SET-4] [Page #11/37]

24.	(a)	Write the output of the code given below:	2
		def short sub (lst,n) :	
		for i in range (0,n) :	
		if len (lst)>4:	
		lst [i]=lst [i]+lst[i]	
		else:	
		lst[i]=lst[i]	
		<pre>subject=['CS','HINDI','PHYSICS','CHEMISTRY','MATHS']</pre>	
		short sub(subject,5)	
		print(subject)	
	Ans	Output:	
		['CSCS','HINDIHINDI','PHYSICSPHYSICS','CHEMISTRYCHEMISTRY','MATHSMATHS']	
		(2 Marks for writing the correct output with or without formatting)	
		OR	
	(b)	Write the output of the code given below:	2
		a =30	
		def call (x):	
		global a	
		if a%2==0:	
		x+=a	
		else:	
		x-=a	
		return x	
		x=20	
		print(call(35),end="#")	
		<pre>print(call(40),end= "@")</pre>	
	Ans.	65#70@	
		(½ marks each for the four components 65, #, 70, @ with or without formatting)	
25.	(a)	Differentiate between CHAR and VARCHAR data types in SQL with appropriate example.	2

[Sub Code: 083 Series: HFG1E Paper Code: 91 SET-4] [Page #12/37]

	(½ Mark each for the two DML commands)	
	DML - INSERT, UPDATE, DELETE, SELECT (OR any two valid DML command) (1/2 Mark each for the two DDL commands)	
(b	DDL - CREATE, ALTER, DROP (OR any two valid DDL command)	2
	OR	2
	(2 Marks for mentioning one difference with the help of examples) OR (1 Mark each for writing explanation of each type with example) OR (1/2 Mark for each term for mentioning only purpose without example)	
	OR any other valid difference and examples	
	OR CHAR data type is used to store strings of fixed length, while the VARCHAR data type is used to store strings of variable-length. Eg, to store 'India', VARCHAR(20) occupies only 5 bytes whereas CHAR(20) occupies 20 bytes.	
	VARCHAR is a variable-length character(string) data type. Declaring VARCHAR (30) means a maximum of 30 characters can be stored but the actual allocated bytes will depend on the length of the entered string. So 'CITY' in VARCHAR (30) will occupy space needed to store 4 characters only and the remaining 26 will be released.	
	CHAR is of fixed length character(string) data type, which means, declaring CHAR (10) implies to reserve spaces for 10 characters. If data does not have 10 characters (e.g., 'CITY' has four characters), MySQL fills the remaining 6 characters with spaces padded on the right.	

[Sub Code: 083 Series: HFG1E Paper Code: 91 SET-4] [Page #13/37]

	SECTION-C									
26	(a)	Consider the following tables - LOAN and BORROWER:								1
		Table: LOAN								
		LOAN_NO	B_NAME		AMOL	JNT				
		L-170	DELHI		3000					
		L-230	KANPUR		4000					
		Table : BORROWER								
		CUST_NAME		LOAN_NO						
		JOHN KRISH		L-171 L-230						
		RAVYA	L-170							
		How many rows and columns will be there in the natural join of these two tables?								
	Ans.	Rows: 2								
		Columns: 4								
		(½ Mark each for correct values of Rows and Columns)								

[Sub Code: 083 Series: HFG1E Paper Code: 91 SET-4] [Page #14/37]

	Write the output of the queries (i) to (iv) based on the table, WORKER given below:								
	TABLE: WORKER								
	W_ID	F_NAM	۸E	L_NAME	CITY	STATE UTTAR PRADESH PUNJAB DELHI			
	102	SAHIL		KHAN	KANPUR				
	104	SAMEE	R	PARIKH	ROOP NAGAR				
	105	MARY		JONES	DELHI				
	106	MAHIR ATHARVA VEDA		SHARMA BHARDWAJ	SONIPAT	HARYANA DELHI UTTAR PRADESH			
	107				DELHI				
	108			SHARMA	KANPUR				
	(i) SELECT F NAME, CITY FROM WORKER ORDER BY STATE DESC;								
	(;)			GERM TRO					
	(i) SEI	LECT F_1	NAME	, CITY FROM	MORKER ORDE	R BY STATE DESC;			
Ans.	(i) SEI		CITY		MORKER ORDE	R BY STATE DESC;			
Ans.				,	I WORKER ORDE	R BY STATE DESC;			
Ans.	F_NAME		CITY	PUR	MORKER ORDE	R BY STATE DESC;			
Ans.	F_NAME SAHIL	=	CITY KANI KANI	PUR	M WORKER ORDE	R BY STATE DESC;			
Ans.	F_NAME SAHIL VEDA	=	CITY KANI KANI	PUR PUR P NAGAR	I WORKER ORDE	R BY STATE DESC;			
Ans.	F_NAME SAHIL VEDA SAMEER	=	CITY KANI KANI ROO	PUR PUR P NAGAR	I WORKER ORDE	R BY STATE DESC;			

[Sub Code: 083 Series: HFG1E Paper Code: 91 SET-4] [Page #15/37]

Ans.	CITY			
	CITY			
	KANPUR			
	ROOP NAGAI	R		
	DELHI			
	SONIPAT			
	(½ Mark for	writing the correct o	ıtput)	
		F_NAME, STATE F		
Ans.				
Ans.	F_NAME	STATE		
Ans.	F_NAME SAHIL	STATE UTTAR PRADESH		
Ans.				
Ans.	SAHIL	UTTAR PRADESH		
Ans.	SAHIL MAHIR	UTTAR PRADESH HARYANA		
Ans.	SAHIL MAHIR ATHARVA	UTTAR PRADESH HARYANA DELHI		

[Sub Code: 083 Series: HFG1E Paper Code: 91 SET-4] [Page #16/37]

Ans	5.					
	CITY	COUNT (*)				
	KANPUR	2				
	ROOP NAGAR	1				
	DELHI	2				
	SONIPAT	1				
	(½ Mark for writh Note for (i) to (i		output)			
	1. Ignore the 2. ½ mark fo output	output header or each query, f	and cases of the outputs or writing any 2 correct rows in the /columns should be ignored.			
27. (a)	reads the content lines from the fill content of 'LINE Once upon a time He lived in a little One day, he was He saw a little git happily. The girl was follows the function He lived in a little git happily.	e girl was followed by a big gray wolf. en the function should display output as: lived in a little house in a beautiful, green wood. saw a little girl skipping through the woods, whistling				

[Sub Code: 083 Series: HFG1E Paper Code: 91 SET-4] [Page #17/37]

```
def LongLines():
Ans.
         myfile=open('LINES.TXT') # ignore 'r' mode
         all lines=myfile.readlines()
         for aline in all lines:
             if(len(aline.split()>=10):
                 print(aline)
         myfile.close()
     OR
     def LongLines():
         with open ('LINES.TXT') as myfile: # ignore 'r' mode
             all lines=myfile.readlines()
             for aline in all lines:
                  if(len(aline.split())>=10):
                     print(aline)
     OR
     def LongLines():
         myfile=open('LINES.TXT') # ignore 'r' mode
         for aline in myfile:
             if(len(aline.split())>=10):
                 print(aline)
         myfile.close()
     OR
     def LongLines():
         myfile=open('LINES.TXT') # ignore 'r' mode
         s1=" "
         while s1:
             s1=myfile.readline()
             words=s1.split()
             if(len(words) >= 10):
                 print(s1)
         myfile.close()
     \mathbf{OR}
     any other valid Python code to serve the purpose.
```

```
(1/2 mark for the function header)
     (1/2 mark for opening the file)
     (1/2 mark for reading the file correctly)
     (1 mark for checking the number of words in each line)
     (½ mark for displaying the desired lines)
                                      OR
     Write a function count_Dwords() in Python to count the words ending with a
(b)
     digit in a text file "Details.txt".
     Example:
     If the file content is as follows:
     On seat2 VIP1 will sit and
     On seat1 VVIP2 will be sitting
     Output will be:
     Number of words ending with a digit are 4
     def count Dwords():
Ans.
        with open ("Details.txt", 'r') as F: # ignore 'r'
               S=F.read()
               Wlist = S.split()
               count = 0
               for W in Wlist:
                   if W[-1].isdigit():
                        count+=1
       print("Number of words ending with a digit are",count)
     OR
     def count Dwords():
        count=0
       myfile=open("Details.txt")
       S=myfile.read()
       Wlist=S.split()
               for W in Wlist:
                   if i[-1] in "0123456789":
                        count=count+1
       myfile.close()
        print("Number of words ending with a digit are",count)
```

[Sub Code: 083 Series: HFG1E Paper Code: 91 SET-4] [Page #19/37]

		OR								
		<pre>def count_Dwords():</pre>								
		<pre>myfile=open("Details.txt") </pre>								
		<pre>count=0 for line in myfile:</pre>								
		s1=line.split()								
		for i in s1:								
		if i[-1] in "0123456789":								
		count=count+1								
		print("Number of words ending with a digit are",count)								
		myfile.close()								
		OR								
		any other valid Python code to serve the purpose.								
		(½ mark foi	the function header	r)						
		(½ mark for opening the file)								
		(½ mark for reading the file correctly)								
		(1 mark for checking the condition)								
		(½ mark for displaying the desired lines)								
28.	(a)		Write the outputs of the SQL queries (i) to (iv) based on the relations COMPUTER and SALES given below :							
		COMPOTENT	and SALLS given below	٧.						
		Table : COMPUTER								
		PROD_ID	PROD_NAME	PRICE	COMPANY	TYPE				
		P001	MOUSE	200	LOGITECH	INPUT				
		P002	LASER PRINTER	4000	CANON	OUTPUT				
		P003	KEYBOARD	500	LOGITECH	INPUT				
		P004	JOYSTICK	1000	IBALL	INPUT				
		P005	SPEAKER	1200	CREATIVE	OUTPUT				
		P006 DESKJET PRINTER 4300 CANON OUTPUT								

[Sub Code: 083 Series: HFG1E Paper Code: 91 SET-4] [Page #20/37]

	Table : SALE	S	
	PROD_ID	QTY_SOLD	QUARTER
	P002	4	1
	P003	2	2
	P001	3	2
	P004	2	1
A 17 7	(i) SELECT	MIN (PRICE)	, MAX (PRICE) FROM COMPUTER;
Ans.	MIN(PRICE)	MAX(PRIC	CE)
	200	4300	
	(½ mark for	correct out	put)
			COUNT(*) FROM COMPUTER GROUP BY COUNT(COMPANY) > 1;
Ans.			
	COMPANY	COUNT((*)
	LOGITECH	2	
	CANON	2	
	(½ mark for	correct out	put)
		_	PROD_ID AND TYPE = 'INPUT';
Ans.		_	
	PROD_NAM	ME QTY_S	SOLD
	MOUSE	3	
	KEYBOARI	2	
	JOYSTICK	2	

[Sub Code: 083 Series: HFG1E Paper Code: 91 SET-4] [Page #21/37]

		(½ mark for corre	(½ mark for correct output)						
		, ,	iv) SELECT PROD_NAME, COMPANY, QUARTER FROM COMPUTER C, SALES S WHERE C.PROD_ID=S. PROD_ID;						
		PROD_NAME	COMPANY	QUARTER					
		MOUSE	LOGITECH	2					
		LASER PRINTER	CANON	1					
		KEYBOARD	LOGITECH	2					
		JOYSTICK	IBALL	1					
		(½ mark for corre	ect output)						
	(b)	Write the comman	d to view all d	atabases.		1			
	Ans.	SHOW DATABASE	ES;						
		(1 mark for writing Note: punctuation	_		e ignored.				
29.			ements all even ta of the list is ,35,55]	n numbers by	accepts a list L of numbers. 1 and decrements all odd	3			
	Ans.	if L[i L[else:	L): ange(len(L)]%2==0: i]=L[i]+1 i]=L[i]-1):					

[Sub Code: 083 Series: HFG1E Paper Code: 91 SET-4] [Page #22/37]

```
OR
def EOReplace():
    L=[]
    ch = 'y'
    while ch == 'y' or ch == 'Y':
         x = int(input('give item'))
         L.append(x)
         ch= input('do you want to enter more y/n ')
    for i in range(len(L)):
         if L[i]%2==0:
             L[i]=L[i]+1
         else:
             L[i]=L[i]-1
    print(L)
OR
def EOReplace():
    L=eval(input("Enter list="))
    Size=len(L)
    for i in range(Size):
         if L[i]%2==0:
             L[i]=L[i]+1
         else:
             L[i]=L[i]-1
    print(L)
OR
any other valid Python code to serve the purpose.
(1/2 mark for correct function header)
(1/2 mark for getting the list)
(1/2 mark for correct loop)
(1/2 mark for checking the condition)
(1/2 mark for incrementing the even values)
(½ mark for decrementing the odd values)
```

[Sub Code: 083 Series: HFG1E Paper Code: 91 SET-4] [Page #23/37]

30.	(a)	A list contains following record of customer:	3
30.		[Customer name, Room Type]	
		Write the following user defined functions to perform given operations on	
		the stack named 'Hotel':	
		the stack named 'Hotel':	
		(i) Push Cust() - To Push customers' names of those customers who are	
		staying in 'Delux' Room Type.	
		(ii) Pop_Cust () - To Pop the names of customers from the stack and	
		display them. Also, display "Underflow" when there are no customers in the	
		stack.	
		For example :	
		For example : If the lists with customer details are as follows :	
		["Siddarth", "Delux"]	
		["Rahul", "Standard"]	
		["Jerry", "Delux"]	
		The stack should contain	
		Jerry	
		Siddharth	
		The output should be:	
		Jerry	
		Siddharth	
		Underflow	
	Ans.	Hotel=[]	
		Customer=[["Siddarth","Delux"],["Rahul","Standard"],["Jer	
		ry", "Delux"]]	
		<pre>def Push_Cust():</pre>	
		for rec in Customer:	
		<pre>if rec[1]=="Delux":</pre>	
		Hotel.append(rec[0])	
		<pre>def Pop Cust():</pre>	
		while len(Hotel)>0:	
		print(Hotel.pop())	
		else:	
		print("Underflow")	
		F (,	

[Sub Code: 083 Series: HFG1E Paper Code: 91 SET-4] [Page #24/37]

```
OR
     top=0
     def Push Cust(Hotel, Customer):
          global top
          for cust rec in Customer:
               if cust rec[1]=="Delux":
                    Hotel.insert(top, cust rec[0])
                    top=top+1
     def Pop Cust (Hotel):
          global top
          while len(Hotel)>0:
               print(Hotel.pop())
               top=top-1
          else:
               print("Underflow")
     OR
     Any other valid Python code to serve the purpose.
     (½ mark for defining correct function header (Push Cust())
     (1/2 mark for correct loop in function Push_Cust())
     (1/2 mark for checking the condition and appending the data in
     Push_Cust())
     (½ mark for defining correct function header (Pop_Cust())
     (1/2 mark for correct loop in function Pop Cust())
     (½ mark for deleting and displaying the data in Pop_Cust())
                                      OR
(b)
     Write a function in Python, Push (Vehicle) where, Vehicle is a
                                                                                   3
     dictionary containing details of vehicles - {Car Name: Maker}.
     The function should push the name of car manufactured by 'TATA'
     (including all the possible cases like Tata, TaTa, etc.) to the stack.
     For example:
     If the dictionary contains the following data:
     Vehicle={"Santro":"Hyundai","Nexon":"TATA","Safari":"Tata"}
     The stack should contain
     Safari
     Nexon
```

[Sub Code: 083 Series: HFG1E Paper Code: 91 SET-4] [Page #25/37]

```
stack=[]
      Ans
            def Push(Vehicle) :
                   for v name in Vehicle :
                         if Vehicle[v name].upper() == "TATA" :
                                stack.append(v name)
            OR
            stack=[]
            def Push (Vehicle) :
               for v name in Vehicle :
                 if Vehicle[v name] in ("TATA", "TaTa", "tata", "Tata"):
                     stack.append(v name)
            OR
            Any other valid Python code to serve the purpose.
            (½ mark for defining correct function header)
            (1/2 mark for correct loop)
            (1 mark for checking the condition)
            (1 mark for appending the data)
                                           SECTION - D
31
            Quickdev, an IT based firm, located in Delhi is planning to set up a network
            for its four branches within a city with its Marketing department in Kanpur.
            As a network professional, give solutions to the questions (i) to (v), after
            going through the branches locations and other details which are given below:
                                                         KANPUR BRANCH
                                 DELHI BRANCH
                                                          MARKETING DEPT.
                                          BRANCH B
                          BRANCH A
                          BRANCH C
                                           BRANCH D
            Distance between various branches is as follows:
              Branch
                                       Distance
              Branch A to Branch B
                                       40 m
              Branch A to Branch C
                                       80 m
                                       65 m
              Branch A to Branch D
              Branch B to Branch C
                                       30 m
              Branch B to Branch D
                                       35 m
              Branch C to Branch D
                                       15 m
              Delhi Branch to Kanpur
                                       300 \text{ km}
```

[Sub Code: 083 Series: HFG1E Paper Code: 91 SET-4] [Page #26/37]

	Branch	Number of Computers	
	Branch A	15	
	Branch B	25	
	Branch C	40	
	Branch D	115	
(i)	Suggest the with a suita	most suitable place to install the server for the Delhi branch ble reason.	
Ans		s it has maximum number of computers er location with valid justification	
	(½ mark fo	or naming the Branch and ½ mark for correct justification)	
(ii)	Suggest an	ideal layout for connecting all these branches within Delhi.	
Ans	BRANCH B BRANCH C (Based on S OR	BRANCH D erver Location)	
	BRANCH (
	· '	ninimum distance between branches)	
	, ,	r correctly drawing any one valid layout)	
	OR (1 mark foi	r correctly suggesting name of any one valid topology)	
(iii)	Which devi	ce will you suggest, that should be placed in each of these	
		efficiently connect all the computers within these branches?	
	branches to	erriclerity connect at the computers within these branches:	

[Sub Code: 083 Series: HFG1E Paper Code: 91 SET-4] [Page #27/37]

		(Deduc		y other additional option o	along with correct	
			ks for the correct ans			
	Ans.	(i)	10#25#15 20#25#25			
			20#25#25		15#20#10#	
		(iii)	30#20#20	(iv)	10#15#25#	
			20#25#25		25#20#15	
		(i)	10#25#15	(ii)	5#25#20	
			print(M[Ilrst], M	[sec], M[third], sep="	# ··)	
			third=random.rand		II 11 N	
			sec=random.randint			
			first=random.rand	int(2 , 5)-1		
		-	10,15,20,25,30] in range(1,3):			
		_	t random			
		of exec	cution of the following	program :		
32	(a)	What p	oossible output(s) are ex	xpected to be displayed on s	screen at the time	2
		,	k for any other valid p Insferring of files)	protocol that can be used	to provide help	
		OR	k for writing the corre	ŕ		
	Ans.	FTP				
	(v)		t a protocol that shall etween Delhi and Kanpu	be needed to provide help ir branch.	for transferring of	1
		(½ ma	rk for correct justifica	ition)		
			rk for writing the corr	ect type of network)		
	Ans.	wan -	•	d across different geographi	cal locations of the	
		MAN w	ill be formed? Justify y			
	(iv)			ct to its Marketing departme		1

[Sub Code: 083 Series: HFG1E Paper Code: 91 SET-4] [Page #28/37]

(b)	The code given below deletes the record from the table employee which contains the following record structure:	3
	E code - String	
	E name - String	
	Sal - Integer	
	City - String	
	Note the following to establish connectivity between Python and MySQL:	
	· Username is root	
	Password is root	
	· The table exists in a MySQL database named emp.	
	• The details (E_code, E_name, Sal, City) are the attributes of the table.	
	Write the following statements to complete the code:	
	Statement 1 - to import the desired library.	
	Statement 2 - to execute the command that deletes the record with	
	E_code as 'E101'.	
	Statement 3 - to delete the record permanently from the database.	
	import as mysql # Statement 1	
	def delete():	
	<pre>mydb=mysql.connect(host="localhost",user="root",</pre>	
	<pre>passwd="root",database="emp")</pre>	
	mycursor=mydb.cursor()	
	# Statement 2	
	# Statement 3	
	print ("Record deleted")	
Ans.	Statement 1: mysql.connector	
	OR any other valid library used for	
	Python MySQL connectivity	
	Statement 2: mycursor.execute("DELETE FROM employee	
	WHERE E_code='E101'")	
	Statement 3: mydb.commit()	
	(1 mark for writing any valid library for Statement 1)	
	(½ mark for writing correct object & function name in Statement 2)	
	(½ mark for writing correct Query in Statement 2)	
	(½ mark for writing correct object name in Statement 3)	
	(½ mark for writing correct function name in Statement 3)	
	, , , , , , , , , , , , , , , , , , , ,	

[Sub Code: 083 Series: HFG1E Paper Code: 91 SET-4] [Page #29/37]

	OR	
(-)	Doe diet the sectors of the seeds given heles	
(a)	Predict the output of the code given below:	2
	<pre>def makenew(mystr) :</pre>	
	newstr=""	
	count=0	
	for i in mystr :	
	if count%2!=0:	
	newstr=newstr+str(count)	
	else :	
	if i.lower():	
	newstr=newstr+i.upper()	
	else:	
	newstr=newstr+i	
	count+=1	
	print(newstr)	
	makenew("No@1")	
Ans.	N1@3	
	(½ mark for writing each correct character with or without formatting)	
(b)	The code given below reads the following records from the table employee and displays only those records who have employees coming from city	
	'Delhi':	
	E_code - String	
	E_name - String	
	Sal - Integer	
	City - String	
	Note the following to establish connectivity between Python and MySQL:	
	• Username is root.	
	Password is root	
	The table exists in a MySQL database named emp.	
	 The details (E_code, E_name, Sal, City) are the attributes of the table. 	

[Sub Code: 083 Series: HFG1E Paper Code: 91 SET-4] [Page #30/37]

		Write the following statements to complete the code: Statement 1 - to import the desired library. Statement 2 - to execute the query that fetches records of the employees coming from city 'Delhi'. Statement 3 - to read the complete data of the query (rows whose city is Delhi) into the object named details, from the table employee in the database.	3
		<pre>import as mysql # Statement 1 def display(): mydb=mysql.connect(host="localhost",user="root", passwd="root",database="emp") mycursor=mydb.cursor() # Statement 2 details =</pre>	
	Ans.	Statement 1: mysql.connector OR any other valid library used for Python MySQL connectivity Statement 2: mycursor.execute("select * from employee where City='Delhi '") Statement 3: mycursor.fetchall()	
		(1 mark for writing any valid library for Statement 1) (½ mark for writing correct object & function name in Statement 2) (½ mark for writing correct Query in Statement 2) (½ mark for writing correct object name in Statement 3) (½ mark for writing correct function name in Statement 3)	
33	(a)	 Write one difference between CSV and text files. Write a program in Python that defines and calls the following user defined functions: COURIER_ADD(): It takes the values from the user and adds the details to a csv file 'courier.csv'. Each record consists of a list with field elements as cid, s_name, Source, destination to store Courier ID, Sender name, Source and destination address respectively. COURIER_SEARCH(): Takes the destination as the input and displays all the courier records going to that destination. 	5

[Sub Code: 083 Series: HFG1E Paper Code: 91 SET-4] [Page #31/37]

```
CSV files
Ans

    can be viewed in spreadsheets

           module CSV has to be imported
     Text files

    can be viewed in the text editor

    No specific module required to be imported

     (any other valid difference - any one)
     import csv
     def COURIER ADD() :
        f1=open("courier.csv", "a", newline="\n")
       writ=csv.writer(f1)
        cid=int(input("Enter the Courier id"))
        s name=input ("Enter the Sender Name")
        Source=input("Enter the Source Address")
        destination=input("Enter Destination Name")
        detail=[cid,s name,Source,destination]
        writ.writerow (detail)
        f1.close()
     def COURIER SEARCH() :
        f1=open("courier.csv","r") # ignore newline
       detail=csv.reader(f1)
       name=input("Enter the Destination Name to be searched")
        for i in detail :
             if i[3] == name:
                   print("Details of courier are: ",i)
     COURIER ADD()
     COURIER SEARCH()
     OR
     Any other valid Python code to serve the purpose.
     (1 mark for any one correct difference between CSV and Text file)
     (1/2 mark for correctly importing csv module)
     (1/2 mark for opening in the file in right mode in COURIER ADD())
     (½ mark for reading values from the user)
     (½ marks correct uses of writerow/writerows)
     (1/2 mark for opening in the file in right mode in COURIER SEARCH())
     (1/2 marks correct uses of reader object)
     (1/2 mark for displaying desired output)
     (1/2 mark for correctly calling COURIER ADD ()
     and COURIER SEARCH())
                                       OR
```

[Sub Code: 083 Series: HFG1E Paper Code: 91 SET-4] [Page #32/37]

(b)	Why is it important to close a file before exiting?	
	Write a program in Python that defines and calls the following user defined functions:	5
	(i) Add_Book(): Takes the details of the books and adds them to a csv file 'Book.csv'. Each record consists of a list with field	
	elements as book_ID, B_name and pub to store book ID, book name and publisher respectively.	
	(ii) Search_Book(): Takes publisher name as input and counts and displays number of books published by them.	
Ans	It is important to close the file before exiting as Python makes sure that any unwritten or unsaved data is flushed off to the file before it is closed.	
	<pre>import csv def Add_Book(): f1=open("Book.csv","a",newline="\n") writ=csv.writer(f1) book_ID=int(input("Enter the Book id")) B_name=input("Enter the Book Name") pub=input("Enter the Publisher Name") detail=[book_ID, B_name,pub] writ.writerow(detail) f1.close() def Search_Book (): f1=open("Book.csv","r") # ignore newline</pre>	
	<pre>fl=open("Book.csv","r") # ignore newline detail=csv.reader(f1) name=input("Enter the Publisher Name to be searched") pub_count=0 for i in detail : if i[2]==name: pub_count+=1 print("NUMBER OF BOOKS: ",pub_count)</pre>	
	Add_Book() Search_Book()	
	OR	
	Any other valid Python code to serve the purpose.	

[Sub Code: 083 Series: HFG1E Paper Code: 91 SET-4] [Page #33/37]

		(½ m (½ m (½ m (½ m (½ m (½ m (½ m	ark for corr ark for oper ark for read arks correct ark for oper arks correct ark for disp	ing correct pur ectly importin ning in the file ding values fro t uses of write ning in the file t uses of reade laying desired	g csv module) in right mode m the user) row/writerow, in right mode r object) output)	o in Add_Book s) o in Search_B	sook())	
34		The s	chool has as	SI ked their estate	ECTION E e manager Mr.	Rahul to main	tain the data	of
				able LAB. Rahu	•			
			LABNO	LAB_NAME	INCHARGE	CAPACITY	FLOOR	
			L001	CHEMISTRY	DAISY	20	I	
		-	L002	BIOLOGY	VENKY	20	II	
			L003	MATH	PREETI	15	I	
			L004	LANGUAGE	DAISY	36	III	
			L005	COMPUTER	MARY KOM	37	II	
		Basec	l on the data	a given above, a	inswer the foll	owing question	ns:	
	(i)	Identify the columns which can be considered as Candidate keys.						
	Ans.	Cand	idate key	s: LABNO and	l LAB_NAME			
		OR	-	ectly writing be	-		ys)	
	(ii)	Write	the degree	and cardinality	of the table.			
	Ans	_	ee = 5	_				
		(½ M		ing value of De ing value of Co				

[Sub Code: 083 Series: HFG1E Paper Code: 91 SET-4] [Page #34/37]

	(iii)	Write the statements to:	2
		(a) Insert a new row with appropriate data.	
		(b) Increase the capacity of all the labs by 10 students which are on 'I'	
		Floor.	
	Ans	(a) INSERT INTO LAB	
		VALUES('L006','PHYSICS','RAVI',25,'II');	
		(b) UPDATE LAB SET CAPACITY=CAPACITY+10 WHERE FLOOR='I';	
		(½ Mark for writing the INSERT INTO LAB part correctly)	
		(½ Mark for writing the VALUES part correctly)	
		(½ Mark for writing the UPDATE LAB SET part correctly)	
		(1/2 Mark for writing the CAPACITY=CAPACITY+10 WHERE FLOOR="I" part correctly)	
		OR	
		(Option for part (iii) only)	
	(iii)	Write the statements to: (a) Add the constraint PRIMARY KEY to a column LABNO in the table. (b) Delete the table LAB.	2
	Ans	(a) ALTER TABLE LAB ADD PRIMARY KEY (LABNO);	
		(b) DROP TABLE LAB;	
		(a) (½ Mark for writing ALTER TABLE LAB part correctly) (½ Mark for writing ADD PRIMARY KEY (LABNO) part correctly)	
		(b) (1 Mark for writing query correctly)	
35		Shreyas is a programmer, who has recently been given a task to write a user defined function named write_bin() to create a binary file called Cust_file.dat containing customer information - customer number (c_no), name (c_name), quantity (qty), price (price) and amount (amt) of each customer.	
		The function accepts customer number, name, quantity and price. Thereafter, it displays the message 'Quantity less than 10 Cannot SAVE', if quantity entered is less than 10. Otherwise the function calculates amount as price * quantity and then writes the record in the form of a list into the binary file.	

[Sub Code: 083 Series: HFG1E Paper Code: 91 SET-4] [Page #35/37]

```
import pickle
      def write bin():
        bin file=
                                   #Statement 1
        while True:
            c no=int(input("enter customer number"))
            c name=input("enter customer name")
           qty=int(input("enter qty"))
           price=int(input("enter price"))
                                   #Statement 2
                 print("Quantity less than 10..Cannot SAVE")
           else:
                 amt=price * qty
                 c detail=[c no,c name,qty,price,amt]
                                   #Statement 3
                 ans=input("Do you wish to enter more records y/n")
                 if ans.lower() == 'n':
                                   #Statement 4
                                   #Statement 5
                                   #Statement 6
      Write the correct statement to open a file 'Cust_file.dat' for writing the data
(i)
      of the customer.
Ans
      Statement 1: open ("Cust file.dat", "wb")
      (1 Mark for correctly writing missing Statement 1)
      Note: 'ab' mode also be considered
      Which statement should Shreyas fill in Statement 2 to check whether quantity
(ii)
                                                                                  1
      is less than 10.
      Statement 2:
Ans
                    qty<10 :
      (1 Mark for correctly writing missing Statement 2)
      Which statement should Shreyas fill in Statement 3 to write data to the binary
                                                                                  2
(iii)
      file and in Statement 4 to stop further processing if the user does not wish to
      enter more records.
Ans
     Statement 3: pickle.dump(c detail,bin file)
      Statement 4: break
      (1 Mark for correctly writing missing Statement 3)
      (1 Mark for correctly writing missing Statement 4)
```

[Sub Code: 083 Series: HFG1E Paper Code: 91 SET-4] [Page #36/37]

	OR	l
	(Option only for part (iii))	İ
(iii)	What should Shreyas fill in Statement 5 to close the binary file named	2
	Cust_file.dat and in Statement 6 to call a function to write data in binary	İ
	file?	
Ans	Statement 5: bin_file.close()	
	Statement 6: write_bin()	,
	(1 Mark for correctly writing missing Statement 5)	
	(1 Mark for correctly writing missing Statement 6)	

[Sub Code: 083 Series: HFG1E Paper Code: 91 SET-4] [Page #37/37]