

SIMPLE HARMONIC MOTION


S.H.M.

$$F = -kx$$

General equation of S.H.M. is $x = A \sin(\omega t + \phi)$; $(\omega t + \phi)$ is phase of the motion and ϕ is initial phase of the motion.

Angular Frequency (ω) :
$$\omega = \frac{2\pi}{T} = 2\pi f$$

Time period (T) :
$$T = \frac{2\pi}{\omega} = 2\pi\sqrt{\frac{m}{k}}$$



Speed :
$$v = \omega\sqrt{A^2 - x^2}$$

Acceleration :
$$a = -\omega^2 x$$



Kinetic Energy (KE) :
$$\frac{1}{2} mv^2 = \frac{1}{2} m\omega^2 (A^2 - x^2) = \frac{1}{2} k (A^2 - x^2)$$


Potential Energy (PE) :
$$\frac{1}{2} Kx^2$$

Total Mechanical Energy (TME)

$$= \text{K.E.} + \text{P.E.} = \frac{1}{2} k (A^2 - x^2) + \frac{1}{2} Kx^2 = \frac{1}{2} KA^2 \text{ (which is constant)}$$

SPRING-MASS SYSTEM

(1)  \Rightarrow  \Rightarrow
$$T = 2\pi\sqrt{\frac{m}{k}}$$

(2) 

$$T = 2\pi\sqrt{\frac{\mu}{K}}, \text{ where } \mu = \frac{m_1 m_2}{(m_1 + m_2)} \text{ known as reduced mass}$$

COMBINATION OF SPRINGS

Series Combination :

$$1/k_{eq} = 1/k_1 + 1/k_2$$

Parallel combination :

$$k_{eq} = k_1 + k_2$$

SIMPLE PENDULUM

$$T = 2\pi \sqrt{\frac{\ell}{g}} = 2\pi \sqrt{\frac{\ell}{g_{eff}}} \quad (\text{in accelerating Refer-}$$

ence Frame); g_{eff} is net acceleration due to pseudo force and gravitational force.

COMPOUND PENDULUM / PHYSICAL PENDULUM

Time period (T) :
$$T = 2\pi \sqrt{\frac{I}{mg\ell}}$$


where, $I = I_{CM} + m\ell^2$; ℓ is distance between point of suspension and centre of mass.

TORSIONAL PENDULUM

Time period (T) :
$$T = 2\pi \sqrt{\frac{I}{C}}$$
 where, C = Torsional constant

Superposition of SHM's along the same direction

$$x_1 = A_1 \sin \omega t \quad \& \quad x_2 = A_2 \sin (\omega t + \theta)$$



If equation of resultant SHM is taken as $x = A \sin (\omega t + \phi)$

$$A = \sqrt{A_1^2 + A_2^2 + 2A_1A_2 \cos \theta} \quad \& \quad \tan \phi = \frac{A_2 \sin \theta}{A_1 + A_2 \cos \theta}$$

1. Damped Oscillation

• Damping force

$$\vec{F} = -b\vec{v}$$

• equation of motion is

$$\frac{mdv}{dt} = -kx - bv$$

• $b^2 - 4mK > 0$ over damping

- $b^2 - 4mK = 0$ critical damping
- $b^2 - 4mK < 0$ under damping
- For small damping the solution is of the form.

$$x = \left(A_0 e^{-bt/2m} \right) \sin [\omega' t + \delta], \text{ where } \omega' = \sqrt{\left(\frac{k}{m} \right) - \left(\frac{b}{2m} \right)^2}$$

For small b

- angular frequency $\omega' \approx \sqrt{k/m}, = \omega_0$

- Amplitude $A = A_0 e^{\frac{-bt}{2m}}$

- Energy $E(t) = \frac{1}{2} K A^2 e^{-bt/m}$

- Quality factor or Q value, $Q = 2\pi \frac{E}{|\Delta E|} = \frac{\omega'}{2\omega_Y}$

where, $\omega' = \sqrt{\frac{k}{m} \cdot \frac{b^2}{4m^2}}, \omega_Y = \frac{b}{2m}$

2. Forced Oscillations And Resonance

External Force $F(t) = F_0 \cos \omega_d t$

$x(t) = A \cos (\omega_d t + \phi)$

$$A = \frac{F_0}{\sqrt{\left(m^2 (\omega^2 - \omega_d^2)^2 + \omega_d^2 b^2 \right)}} \text{ and } \tan \phi = \frac{-v_0}{\omega_d x_0}$$

(a) Small Damping $A = \frac{F_0}{m(\omega^2 - \omega_d^2)}$

(b) Driving Frequency Close to Natural Frequency $A = \frac{F_0}{\omega_d b}$